

WHAT IS CLAIMED IS:

1. A method for forming a composite structure, the method comprising:
applying a primer to a surface of a tool;
applying a coating to the primer;
5 curing the primer and coating applied to the tool; and
forming the composite structure on the tool.
2. The method of Claim 1 wherein the tool is a metallic material.
- 10 3. The method of Claim 1 wherein the tool is a composite material.
4. The method of Claim 1 wherein the primer is a powdered primer.
5. The method of Claim 1 wherein the primer is a nylon powder primer.
- 15 6. The method of Claim 1 wherein the coating is a powdered fluorinated
organic compound.
7. The method of Claim 1 wherein at least one of the applying steps
20 comprises electrostatic powder spraying.
8. The method of Claim 1 wherein the forming step comprises placing the
tool in an oven and heating the oven.
- 25 9. The method of Claim 1 further comprising the step of cleaning the
surface of the tool with a solvent before applying the primer.
10. The method of Claim 9 wherein the solvent is an isopropyl alcohol.
- 30 11. The method of Claim 1 further comprising the step of coupling tape to
a peripheral portion of the surface before applying the primer.

12. The method of Claim 3, further comprising the step of applying a surfactant solution to the surface before applying the primer.

5 13. A method for forming a composite structure, the method comprising:
 cleaning a surface of a tool, the surface having a peripheral portion;
 covering the peripheral portion;
 applying a primer to the uncovered portion of the surface;
 applying a coating to the primer;
 curing the primer and coating applied to the tool; and
 forming the composite structure on the tool.

10 14. The method of Claim 13 wherein the tool is a steel mold for forming
 composite structures.

 15. The method of Claim 13 wherein the tool is a composite mold for
 forming composite structures.

15 16. The method of Claim 13 wherein the primer is a powdered primer.

 17. The method of Claim 13 wherein the primer is a nylon powder primer.

20 18. The method of Claim 13 wherein the coating is a powdered fluorinated
 organic compound.

 19. The method of Claim 13 wherein at least one of the applying steps
 comprises electrostatic powder spraying.

25 20. The method of Claim 13 wherein the forming step comprises placing
 the tool in an oven and heating the oven to at least 450 degrees Fahrenheit.

 21. The method of Claim 13 wherein the cleaning step comprises applying
 a solvent to the surface of the tool.

30 22. The method of Claim 21 wherein the solvent is an isopropyl alcohol.

23. The method of Claim 13 wherein the covering step comprises coupling masking tape to the peripheral portion of the surface.

5 24. The method of Claim 15, further comprising the step of applying a surfactant solution to the surface after cleaning the surface of the tool.